


MODEL	HQWY30GF	
Prime Power(50Hz)	30KW	37.5KVA
Standby Power(50Hz)	33KW	41.25KVA

Standard Features

General Features:

- ◆ Engine (Weichai Yangchai Series WP3.9D33E2)
- ◆ Radiator 40°C max, fans are driven by belt, with safety guard
- ◆ 12V charge alternator
- ◆ Alternator: single bearing alternator IP23, insulation class H/H
- ◆ Absorber
- ◆ Dry type air filter, fuel filter, oil filter
- ◆ Main line circuit breaker
- ◆ Standard control panel
- ◆ Batteries, rack and cable
- ◆ Ripple flex exhaust pipe, exhaust siphon, flange, muffler
- ◆ User manual



Generator Ratings

Voltage(V)		Hz	Phase	P.F (cos φ)	Prime Amps (A)	Prime Ratings (KW/KVA)	
440	254	50	3	0.8	49.21	30	37.5
415	240	50	3	0.8	52.17	30	37.5
400	230	50	3	0.8	54.13	30	37.5
380	220	50	3	0.8	56.98	30	37.5

●Prime Power (PRP): Prime power is available for an unlimited number of annual hours in variable load application, in accordance with GB/T2820-97 (eqv ISO8528) ; A 10% overload capability is available for a period of 1 hour within a 12-hour period of operation.

●Standby Power Rating (ESP): The standby power rating is applicable for supplying emergency power for the duration of a utility power interruption. No overload, utility parallel or negotiated outage operation capability is available at this rating.

Standard Features

Huaquan Power provides a full line of brand new and high quality products. Each and every unit is strictly factory tested. Warranty is according to our standard conditions: ①12 months, counted on the day Huaquan sold to the first buyer; ② One year after installation; ③ 1000 running hours (accumulated); subject to the earlier one. Service and parts are available from Huaquan Power or distributors in your location.

Engine Data

Manufacturer / Model: Weichai Yangchai Series WP3.8D33E2, 4-stroke
Air Intake System: Naturally intake
Type: Four-stroke、 Direct injection、 4 Cylinders、 Wet cylinder、 Water cooling
Cylinder Type: Water-cooled cylinder liner
Start mode: Electric starting
Cooling mode: Closed water cooling
Displacement: 3.86
Bore and Stroke: 102*118(mm)
Compression Ratio: 17.5:1
Rated RPM: 1500rpm
Max. Standby Power: 33.3KW
Governor Type: Electronic / Mechanical

Exhaust system

Max Back Pressure: 10kPa

Air Intake System

Max Intake Restriction: 5kPa

Fuel System

100%(Prime Power) Load: $\leq 230\text{g/kw.h}$

Oil System

Total Oil Capacity: 10L
Oil Consumption: $\leq 0.8\text{g/kwh}$

Cooling System

Total Coolant Capacity: 18L

Alternator Specification

Compliance with GB755, BS5000, VDE0530, NEMAMG1-22, IED34-1, CSA22.2 and AS1359 standards.

Alternator Data

Manufacturer: STAMFORD/MARATHON/ LEROY-SOMER/HUAQUAN
Number of Phase: 3
Connecting Type: 3 phase and 4 wires,"Y" type connecting

Number of bearing: 1
Power factor: 0.8
Protection grade: IP23 option, upon request
Altitude : $\leq 1000\text{m}$
Exciter type: Brushless, self-exciting
Insulation class: H
Telephone influence factor(TIF): ≤ 50
THF: $\leq 2\%$
Alternator Capacity: 30KW/37.5KVA
Alternator Efficiencies: 85%
Air Cooling Flow: 0.09m³/s
Adjusting rate of stable voltage: $\pm 0.5\%$

Generating Set Data

Voltage Regulation: $\geq \pm 5\%$
Voltage Regulation, Stead State: $\leq \pm 1\%$
Sudden Voltage Warp: $\leq +20\%$
Sudden Voltage Warp: $\leq -15\%$
Voltage Stable Time: $\leq 5\text{S}$
Voltage unbalance: $\leq 1\%$
Frequency Regulation, Stead State: $\leq 5\%$
Frequency Waving: $\leq 0.5\%$
Sudden Frequency Warp: $\leq +10\%$
Transient frequency deviation: $\leq -7\%$
Frequency Recovery Time: $\leq 3\text{S}$


Standard Features

- | | | |
|--------------------------------|------------------|-------------------|
| ◆ Standard Auto Control System | ◆ MCCB | ◆ Special tool |
| ◆ Starting batteries | ◆ Battery switch | ◆ Oil Drain Valve |
| ◆ Exhaust System | ◆ Shock pad | ◆ Documents |

Options

Engine:	◇ Engine Heater	◇ Battery Charger	◇ Air preheater
Alternator:	◇ Alternator Heater	◇ PMG	
Electrical System:	◇ Remote Control Panel	◇ Automatic Transfer Switch	◇ Paralleling System
Type:	◇ Rainproof Type	◇ Soundproof Type	◇ Trailer Type
Other:	◇ Spare Parts	◇ Daily Fuel Tank	

Dimension & Weight



Open Type

Overall Size: 1600(mm)× 600 (mm) ×1100 (mm)

Weight: 700kg

Soundproof Type

Overall Size:2300 (mm) ×900 (mm) ×1500 (mm)

Weight: 950kg

Standard Control Panel



Huaquan Power uses micro processing technique integrating digital, intelligent and network techniques which can carry out functions including auto start/stop, data measure, alarming. The controller uses Smartgen LCD display, optional Chinese and English/ Russian/ Spanish display interface with operation easy and reliable. It can be widely used in all types of generator automatic control system for compact structure, advanced circuits, simple connections and high reliability.

Typical Projects

